

MULTI-CAPILLARY DNA SEQUENCER

Patent Number: JP9243597
Publication date: 1997-09-19
Inventor(s): NAKAMURA SHIN; NAKAMURA KENJI
Applicant(s): SHIMADZU CORP
Requested Patent: ■ JP9243597
Application Number: JP19960080750 19960308
Priority Number(s):
IPC Classification: G01N27/447 ; G01N33/50
EC Classification:
Equivalents:

Abstract

PROBLEM TO BE SOLVED: To enhance processing capability in a multi-capillary DNA sequencer furthermore.

SOLUTION: The exciting optical beams E emitted from lasers 3a and 3b enter a detecting part 2 in parallel with the scanning direction. The beams are applied on DNA fragments migrating in a capillary 1a by an objective lens 11, and the fluorescent mark is excited. The fluorescence from the excited DNA fragment is condensed at the objective lens 1 and diaphragmed by a condenser lens 13. The image is formed on a concave grating 16 by a concave mirror 14 through a pinhole 15. The spectrum obtained by spectroscoping at the concave grating 16 is detected by a detector 17, and the kind of end base of the DNA fragment is determined. A CPU 5 recognizes in which capillary the detected signal is located by accepting the signal from the detector 17 in synchronization with the scanning of the detecting part 2.

Data supplied from the esp@cenet database - 12